

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 11

SDS No.: 374519

V007.0 Revision: 01.12.2016

printing date: 02.01.2018

Replaces version from: 18.06.2015

LOCTITE STYCAST 1266 PTB known as STYCAST 1266 PTB 7 OZ QT

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE STYCAST 1266 PTB known as STYCAST 1266 PTB 7 OZ QT

#### **Contains:**

3,3'-Oxybis(ethyleneoxy)bis(propylamine)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Epoxy adhesive

### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification (CLP):

Skin corrosion Category 1B

H314 Causes severe skin burns and eye damage.

Skin sensitizer Category

H317 May cause an allergic skin reaction.

#### 2.2. Label elements

### Label elements (CLP):



Signal word: Danger

Page 2 of 11

MSDS-No.: 374519

V007.0

Hazard statement:	H314 Causes severe skin burns and eye damage.
	H317 May cause an allergic skin reaction.
Precautionary statement:	P280 Wear protective gloves/protective clothing/eye protection/face protection.
Prevention	
Precautionary statement:	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.
_	· · · · · · · · · · · · · · · · · · ·
Response	Rinse skin with water/ shower.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P310 Immediately call a POISON CENTER or doctor.
	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

#### 2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### General chemical description:

Adhesive

### Base substances of preparation:

organic amine

### Declaration of the ingredients according to CLP (EC) No 1272/2008:

	Hazardous components	EC Number	content	Classification
	CAS-No.	REACH-Reg No.		
	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	224-207-2	50- 100 %	Skin Corr. 1B
	4246-51-9	01-2119963377-26		H314
				Skin Sens. 1
ı				H317

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

Inhalation:

Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eve contact

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

SKIN: Rash, Urticaria.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media:

water, carbon dioxide, foam, powder

#### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### **Additional information:**

In case of fire, keep containers cool with water spray.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

#### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

### 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

### Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

### 7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Keep container tightly sealed.

Store at room temperature.

# 7.3. Specific end use(s)

Epoxy adhesive

MSDS-No.: 374519 V007.0

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# **Occupational Exposure Limits**

Valid for

Great Britain

None

# **Occupational Exposure Limits**

Valid for

Ireland

None

# **Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental	Exposure	Value				Remarks
	Compartment	period					
			mg/l	ppm	mg/kg	others	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (freshwater)					0,22 mg/L	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (marine water)					0,022 mg/L	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (intermittent releases)					2,2 mg/L	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sewage treatment plant (STP)					125 mg/L	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sediment (freshwater)				1,1 mg/kg		
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sediment (marine water)				0,11 mg/kg		
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	soil				0,091 mg/kg		

# **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Long term exposure - systemic effects		59 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Acute/short term exposure - systemic effects		176 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Long term exposure - local effects		13 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	dermal	Long term exposure - systemic effects		8,3 mg/kg bw/day	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Long term exposure - systemic effects		17 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Acute/short term exposure - systemic effects		52 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Long term exposure - local effects		0,5 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Acute/short term exposure - local effects		6,5 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	dermal	Long term exposure - systemic effects		5 mg/kg bw/day	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	oral	Long term exposure - systemic effects		5 mg/kg bw/day	

#### **Biological Exposure Indices:**

None

# 8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

## Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

### Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

B 7 OZ QT Page 6 of 11

MSDS-No.: 374519 V007.0

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance liquid liquid

yellow

Odor amine-like

Odour threshold No data available / Not applicable

pH No data available / Not applicable
Initial boiling point No data available / Not applicable
Flash point No data available / Not applicable
Decomposition temperature No data available / Not applicable
Vapour pressure No data available / Not applicable

Density 1,01 g/cm3

()
Bulk density
No data available / Not applicable
Viscosity
No data available / Not applicable
Viscosity (kinematic)
No data available / Not applicable
Explosive properties
No data available / Not applicable

Solubility (qualitative) Soluble

(Solvent: Water)

Solidification temperature No data available / Not applicable No data available / Not applicable Melting point Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable No data available / Not applicable Explosive limits No data available / Not applicable Partition coefficient: n-octanol/water Evaporation rate No data available / Not applicable Vapor density No data available / Not applicable No data available / Not applicable Oxidising properties

#### 9.2. Other information

No data available / Not applicable

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Reacts with alcohols and amines.

Reacts with oxidants, acids and lyes

Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.

### 10.2. Chemical stability

Stable under recommended storage conditions.

# 10.3. Possibility of hazardous reactions

See section reactivity

# 10.4. Conditions to avoid

No decomposition if stored and applied as directed.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

Hydrocarbons carbon oxides. nitrogen oxides

Rapid polymerisation may generate excessive heat and pressure.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### Oral toxicity:

May cause irritation to the digestive tract.

### Inhalative toxicity:

May cause irritation to respiratory system.

#### Skin irritation:

Causes severe skin burns and eye damage.

### Eye irritation:

Corrosive

Avoid eye contact.

### Sensitizing:

May cause an allergic skin reaction.

### Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
3,3'-	LD50	3.160 mg/kg	oral		rat	OECD Guideline 401 (Acute
Oxybis(ethyleneoxy)bis(p						Oral Toxicity)
ropylamine)						
4246-51-9						

# Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time	_	

# Acute dermal toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
3,3'-	Acute	2.500 mg/kg	dermal			Expert judgement
Oxybis(ethyleneoxy)bis(p	toxicity					
ropylamine)	estimate					
4246-51-9	(ATE)					
3,3'-	LD50	> 2.150 mg/kg			rat	OECD Guideline 402 (Acute
Oxybis(ethyleneoxy)bis(p						Dermal Toxicity)
ropylamine)						
4246-51-9						

### Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
3,3'-	corrosive		rabbit	OECD Guideline 404 (Acute
Oxybis(ethyleneoxy)bis(p				Dermal Irritation / Corrosion)
ropylamine)				
4246-51-9				

### Germ cell mutagenicity:

Hazardous components	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		
3,3'-	negative	in vitro mammalian	with and without		OECD Guideline 487 (In vitro
Oxybis(ethyleneoxy)bis(p		cell micronucleus			Mammalian Cell
ropylamine)		test			Micronucleus Test)
4246-51-9					
	negative	mammalian cell	with and without		OECD Guideline 476 (In vitro
		gene mutation assay			Mammalian Cell Gene
					Mutation Test)
	negative	bacterial reverse	with and without		OECD Guideline 471
	_	mutation assay (e.g			(Bacterial Reverse Mutation
		Ames test)			Assay)

# Reproductive toxicity:

Hazardous substances CAS-No.	Result / Classification	Species	Exposure time	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	NOAEL P = 600 mg/kg	screening oral: gavage		rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)

# Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	NOAEL=< 100 mg/kg	oral: gavage	59 daysdaily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

# **SECTION 12: Ecological information**

# General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

# 12.1. Toxicity

#### **Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	LC50	> 215 - 464 mg/l	Fish	96 h	Leuciscus idus	DIN 38412-15
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	EC50	218 mg/l	Daphnia	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	EC50	666 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
1210 31 7	NOEC	15,6 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	EC10	152,5 mg/l	Bacteria	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshe mm-Test)

# 12.2. Persistence and degradability

### Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		
3,3'-	not inherently	aerobic	< 20 %	OECD Guideline 302 B (Inherent
Oxybis(ethyleneoxy)bis(propy	biodegradable			biodegradability: Zahn-
lamine)	-			Wellens/EMPA Test)
4246-51-9				
	Not readily	aerobic	0 %	OECD Guideline 301 B (Ready
	biodegradable.			Biodegradability: CO2 Evolution
				Test)

### 12.3. Bioaccumulative potential / 12.4. Mobility in soil

# **Mobility:**

Cured adhesives are immobile.

# **Bioaccumulative potential:**

No data available.

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	-1,25				25 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)

# 12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
4246-51-9	Bioaccumulative (vPvB) criteria.

### 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

#### Product disposal:

Dispose of in accordance with local and national regulations.

Collection and delivery to recycling enterprise or other registered elimination institution.

### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

#### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

# **SECTION 14: Transport information**

### 14.1. UN number

ADR	2735
RID	2735
ADN	2735
IMDG	2735
IATA	2735

### 14.2. UN proper shipping name

ADR AN	MINES, LIQUID.	, CORROSIVE,	N.O.S.	(3,3'-
--------	----------------	--------------	--------	--------

oxybis(ethyleneoxy)bis(propylamine))

RID AMINES, LIQUID, CORROSIVE, N.O.S. (3,3'-

oxybis(ethyleneoxy)bis(propylamine))

ADN AMINES, LIQUID, CORROSIVE, N.O.S. (3,3'-

oxybis (ethyleneoxy) bis (propylamine))

IMDG AMINES, LIQUID, CORROSIVE, N.O.S. (3,3'-

oxybis(ethyleneoxy)bis(propylamine))

IATA Amines, liquid, corrosive, n.o.s. (3,3'-oxybis(ethyleneoxy)bis(propylamine))

# 14.3. Transport hazard class(es)

ADR	8
RID	8
ADN	8
IMDG	8
IATA	8

#### 14.4. Packing group

A DD	TT
ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

### 14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

### 14.6. Special precautions for user

ADR not applicable

MSDS-No.: 374519

V007.0

Tunnelcode: (E)

RID not applicable
ADN not applicable
IMDG not applicable
IATA not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC)

100 %

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.