

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

**1 Identification**

- **Product identifier**
- **Trade Name:** 7031
- **Article number:** 7031
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Von Roll USA, Inc.  
200 Von Roll Drive  
SCHENECTADY, NY 12306  
USA
- **Information department:** Environmental Health and Safety Department
- **Emergency telephone number:**  
During normal opening hours (day-time): +1 (518) 344-7100  
Mahoney 24 hours Emergency Message Service to contact EHS: +1 (518) 793-7788  
For Hazardous Materials [or Dangerous Goods] Incident  
Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC :+1 703-741-5970 / 1-800-424-9300

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1A

H350 May cause cancer.

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 1)

· **Hazard pictograms**



GHS02    GHS07    GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

ethanol  
ethylbenzene  
Naphtha (petroleum), hydrotreated light  
4-methylpentan-2-one  
Formaldehyde

· **Hazard statements**

H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P264 Wash thoroughly after handling.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P321 Specific treatment (see on this label).  
P314 Get medical advice/attention if you feel unwell.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P363 Wash contaminated clothing before reuse.  
P370+P378 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023


**Trade Name: 7031**

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT: Not applicable.**
- **vPvB: Not applicable.**

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description: Mixture of the substances listed below with nonhazardous additions.**

· **Dangerous components:**

64-17-5	ethanol	>25-≤50%
67-64-1	acetone	>10-<20%
1330-20-7	xylene	>10-≤25%
27360-07-2	Polyvinyl butyral	>10-≤25%
100-41-4	ethylbenzene	≥0.1-≤2.5%
67-56-1	methanol	≤2.5%
108-10-1	4-methylpentan-2-one	≥0.1-≤2.5%
64742-49-0	Naphtha (petroleum), hydrotreated light	≥0.1-≤2.5%
50-00-0	Formaldehyde	≥0.1-<1%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 3)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

64-17-5	ethanol	1,800 ppm
67-64-1	acetone	200 ppm
1330-20-7	xylene	130 ppm
27360-07-2	Polyvinlyl butyral	30 mg/m <sup>3</sup>
100-41-4	ethylbenzene	33 ppm
67-56-1	methanol	530 ppm
108-10-1	4-methylpentan-2-one	75 ppm
141-78-6	ethyl acetate	1,200 ppm
64742-49-0	Naphtha (petroleum), hydrotreated light	1,000 mg/m <sup>3</sup>
50-00-0	Formaldehyde	0.90 ppm

### · PAC-2:

64-17-5	ethanol	3300* ppm
67-64-1	acetone	3200* ppm
1330-20-7	xylene	920* ppm

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 4)

27360-07-2	Polyvinlyl butyral	330 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1100* ppm
67-56-1	methanol	2,100 ppm
108-10-1	4-methylpentan-2-one	500 ppm
141-78-6	ethyl acetate	1,700 ppm
64742-49-0	Naphtha (petroleum), hydrotreated light	11,000 mg/m <sup>3</sup>
50-00-0	Formaldehyde	14 ppm

## · PAC-3:

64-17-5	ethanol	15000* ppm
67-64-1	acetone	5700* ppm
1330-20-7	xylene	2500* ppm
27360-07-2	Polyvinlyl butyral	2,000 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1800* ppm
67-56-1	methanol	7200* ppm
108-10-1	4-methylpentan-2-one	3000* ppm
141-78-6	ethyl acetate	10000** ppm
64742-49-0	Naphtha (petroleum), hydrotreated light	66,000 mg/m <sup>3</sup>
50-00-0	Formaldehyde	56 ppm

## 7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

## \* 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

(Contd. on page 6)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 5)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

<b>64-17-5 ethanol</b>	
PEL	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm
TLV	Short-term value: 1000 ppm A3
<b>67-64-1 acetone</b>	
PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI
<b>1330-20-7 xylene</b>	
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4
<b>100-41-4 ethylbenzene</b>	
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3
<b>67-56-1 methanol</b>	
PEL	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin
TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI
<b>108-10-1 4-methylpentan-2-one</b>	
PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 75 ppm Long-term value: 20 ppm BEI, A3

(Contd. on page 7)

US

## Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 6)

**50-00-0 Formaldehyde**

PEL	Short-term value: 2 ppm Long-term value: 0.75 ppm see 29 CFR 1910.1048(c)
REL	Long-term value: 0.016 ppm Ceiling limit value: 0.1* ppm *15-min; See Pocket Guide App. A
TLV	Short-term value: 0.3 ppm Long-term value: 0.1 ppm DSEN; RSEN, A1

**· Ingredients with biological limit values:****67-64-1 acetone**

BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**100-41-4 ethylbenzene**

BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	---

**67-56-1 methanol**

BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----	---

**108-10-1 4-methylpentan-2-one**

BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

(Contd. on page 8)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 7)

· **Breathing equipment:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*

· **Protection of hands:**



Protective gloves

*Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

· **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

· **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

<b>Form:</b>	Fluid
<b>Color:</b>	Amber colored
<b>Odor:</b>	Aromatic
<b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	56 °C (132.8 °F)

· **Flash point:** -4.4 °C (24.1 °F)

· **Flammability (solid, gaseous):** Highly flammable.

· **Auto igniting:** 425 °C (797 °F)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

**Trade Name: 7031**

(Contd. of page 8)

<b>· Danger of explosion:</b>	<i>Product is not explosive. However, formation of explosive air/vapor mixtures are possible.</i>
<b>· Explosion limits:</b>	
<b>Lower:</b>	<i>Not determined.</i>
<b>Upper:</b>	<i>Not determined.</i>
<b>· Vapor pressure:</b>	<i>Not determined.</i>
<b>· Density at 20 °C (68 °F):</b>	<i>0.88072 g/cm<sup>3</sup> (7.34961 lbs/gal)</i>
<b>· Relative density</b>	<i>Not determined.</i>
<b>· Vapor density</b>	<i>Not determined.</i>
<b>· Evaporation rate</b>	<i>Not determined.</i>
<b>· Solubility in / Miscibility with Water:</b>	<i>Not miscible or difficult to mix.</i>
<b>· Partition coefficient (n-octanol/water):</b>	<i>Not determined.</i>
<b>· Viscosity:</b>	
<b>Dynamic:</b>	<i>Not determined.</i>
<b>Kinematic:</b>	<i>Not determined.</i>
<b>· Solvent content:</b>	
<b>Organic solvents:</b>	<i>67.2 %</i>
<b>Water:</b>	<i>0.2 %</i>
<b>VOC content:</b>	<i>53.94 %</i>
	<i>714.2 g/l / 5.96 lb/gal</i>
<b>· Other information</b>	<i>No further relevant information available.</i>

## 10 Stability and reactivity

- Reactivity** *No further relevant information available.*
- Chemical stability**
- Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- Possibility of hazardous reactions** *No dangerous reactions known.*
- Conditions to avoid** *No further relevant information available.*
- Incompatible materials:** *No further relevant information available.*
- Hazardous decomposition products:** *No dangerous decomposition products known.*

## 11 Toxicological information

- Information on toxicological effects**
- Acute toxicity:**

<b>· LD/LC50 values that are relevant for classification:</b>		
<b>ATE (Acute Toxicity Estimate)</b>		
<i>Dermal</i>	<i>LD50</i>	<i>15,480 mg/kg (rabbit)</i>
<i>Inhalative</i>	<i>LC50/4 h</i>	<i>55.2 mg/l</i>

(Contd. on page 10)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 9)

<b>64-17-5 ethanol</b>		
Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)
<b>67-64-1 acetone</b>		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
<b>1330-20-7 xylene</b>		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
<b>100-41-4 ethylbenzene</b>		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
<b>67-56-1 methanol</b>		
Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)
<b>108-10-1 4-methylpentan-2-one</b>		
Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (ATE) 8.3-16.6 mg/l (rat)

• **Primary irritant effect:**

• **on the skin:** Irritant to skin and mucous membranes.

• **on the eye:** Irritating effect.

• **Sensitization:** Sensitization possible through skin contact.

• **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

• **Carcinogenic categories**

• <b>IARC (International Agency for Research on Cancer)</b>		
64-17-5	ethanol	I
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
108-10-1	4-methylpentan-2-one	2B
50-00-0	Formaldehyde	I

• **NTP (National Toxicology Program)**

50-00-0	Formaldehyde	K
---------	--------------	---

• **OSHA-Ca (Occupational Safety & Health Administration)**

50-00-0	Formaldehyde	
---------	--------------	--

US

(Contd. on page 11)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 10)


**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- |   |                     |
|---|---------------------|
| · <b>UN-Number</b>  |                     |
| · <b>DOT, IMDG, IATA</b>  | UN1133              |
| · <b>UN proper shipping name</b>  |                     |
| · <b>DOT, IATA</b>  | Adhesives           |
| · <b>IMDG</b>   | ADHESIVES           |
| · <b>Transport hazard class(es)</b>   |                     |
| · <b>DOT</b>  |                     |
|  |                     |
| · <b>Class</b>  | 3 Flammable liquids |
| · <b>Label</b>  | 3                   |

(Contd. on page 12)


**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 11)

· <b>IMDG, IATA</b>	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	II
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
-----	
· <b>IMDG</b>	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, II

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):	
50-00-0	Formaldehyde
· Section 313 (Specific toxic chemical listings):	
1330-20-7	xylene
100-41-4	ethylbenzene
67-56-1	methanol
108-10-1	4-methylpentan-2-one
50-00-0	Formaldehyde
· TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	

(Contd. on page 13)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 12)

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
67-56-1	methanol
108-10-1	4-methylpentan-2-one
50-00-0	Formaldehyde

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
108-10-1	4-methylpentan-2-one
50-00-0	Formaldehyde

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5	ethanol
67-56-1	methanol
108-10-1	4-methylpentan-2-one

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
108-10-1	4-methylpentan-2-one	I
50-00-0	Formaldehyde	B1

· **TLV (Threshold Limit Value)**

64-17-5	ethanol	A3
67-64-1	acetone	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
50-00-0	Formaldehyde	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

50-00-0	Formaldehyde
---------	--------------

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS07

GHS08

(Contd. on page 14)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 13)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*ethanol*  
*ethylbenzene*  
*Naphtha (petroleum), hydrotreated light*  
*4-methylpentan-2-one*  
*Formaldehyde*

· **Hazard statements**

*H225 Highly flammable liquid and vapor.*  
*H315 Causes skin irritation.*  
*H319 Causes serious eye irritation.*  
*H317 May cause an allergic skin reaction.*  
*H340 May cause genetic defects.*  
*H350 May cause cancer.*  
*H373 May cause damage to the hearing organs through prolonged or repeated exposure.*

· **Precautionary statements**

*P201 Obtain special instructions before use.*  
*P202 Do not handle until all safety precautions have been read and understood.*  
*P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*  
*P233 Keep container tightly closed.*  
*P240 Ground/bond container and receiving equipment.*  
*P241 Use explosion-proof electrical/ventilating/lighting/equipment.*  
*P242 Use only non-sparking tools.*  
*P243 Take precautionary measures against static discharge.*  
*P260 Do not breathe dust/fume/gas/mist/vapors/spray.*  
*P264 Wash thoroughly after handling.*  
*P272 Contaminated work clothing must not be allowed out of the workplace.*  
*P280 Wear protective gloves/protective clothing/eye protection/face protection.*  
*P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*  
*P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*  
*P308+P313 IF exposed or concerned: Get medical advice/attention.*  
*P321 Specific treatment (see on this label).*  
*P314 Get medical advice/attention if you feel unwell.*  
*P362+P364 Take off contaminated clothing and wash it before reuse.*  
*P333+P313 If skin irritation or rash occurs: Get medical advice/attention.*  
*P337+P313 If eye irritation persists: Get medical advice/attention.*  
*P363 Wash contaminated clothing before reuse.*  
*P370+P378 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.*  
*P403+P235 Store in a well-ventilated place. Keep cool.*  
*P405 Store locked up.*  
*P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **National regulations:**

· **Information about limitation of use:**

*Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.*

(Contd. on page 15)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 08/29/2023

Reviewed on 08/17/2023

Trade Name: 7031

(Contd. of page 14)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### \* 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases** Shelf life: 365 days at room temperature and not recommended at cold room temperature

· **Department issuing SDS:** Environment Health and Safety Department

· **Contact:** Hitesh Surti

· **Date of preparation / last revision** 08/17/2023

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B

Carcinogenicity 1A: Carcinogenicity – Category 1A

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

· **\* Data compared to the previous version altered.**

US